

上海沪析实业有限公司 SHANGHAIHUXIINDUSTRIALCO.,LTD.



Hr-750drh electric lifting

1、产品应用

Product Applications:

• HR-750DRH Electric Lifting Emulsifier is a new high performance product developed by our company according

to the trend of international advanced emulsification equipment. This equipment integrates the functions of dispersion

/mixing/emulsification/homogenization into one. High efficiency, good mixing effect, easy to clean. Simple and convenient



上海沪析实业有限公司 SHANGHAIHUXIINDUSTRIALCO.,LTD.

to lift and lower. Widely used in factories, scientific research institutions, colleges and universities and medical units and other liquid in the material dispersion / mixing / emulsification / homogenization.

• High-shear emulsifier is efficient, fast and uniform distribution of one or more phases into another continuous phase,

while in general the individual phases are insoluble in each other. As the rotor rotates at high speed generated by the high

tangential speed and high-frequency mechanical effect brings strong kinetic energy, so that the insoluble solid phase,

liquid phase, gas phase in the corresponding mature process and the appropriate amount of additives under the joint action,

instant uniform fine dispersion emulsification, after high-frequency cycle, and finally get a stable high-quality products.

Product features:

• The choice of three-phase asynchronous motor, no spark/dust, higher safety performance,

low noise, sufficient power, can work for a long time running, easily meet the semi-production requirements of a variety of high requirements of dispersion and mixing:

 220V/380V power supply can be selected to meet different working environments;

The emulsifying head is finely processed, which makes the operation more stable and durable, and the discharge effect is better.

- High viscosity of materials can be handled, and can work continuously for a long time;
- The base and distribution cabinet are designed with high quality stainless steel shell,

avoiding cleaning resistance and rusting due to material staining in the process of use.



上海沪析实业有限公司 SHANGHAIHUXIINDUSTRIALCO.,LTD.

Product parameters:	
Model	HR-750DRH
Voltage(V)	220V
Motor power(W)	750W
Speed range(rpm)	0~10000rpm
Speed display	stepless
Working head length(mm)	300mm
Lifting system	electric lifting platform, smooth lifting
Lifting distance(mm)	300mm
Capacity(L)	10L
Electric lifting platform	750W Smooth lifting
Exterior Dimension(mm)	450*330*700mm